

REPIPE

Pipe Connections & Valves

22 Spencer St
Five Dock NSW 2046



p: 02 9879 0933

f: 02 9879 3314

e: sales@repipe.com.au

w: repipe.com.au

Technical & Material Safety Data Sheet

Product Identification:	Ducco Teflon Tape	
Product Name:	Yellow Gasline PTFE Tape Pink Waterline PTFE Tape	
Industrial Usage:	Civil-Construction, Machinery, Chemicals & Space Navigation. Water supply & Fire Systems.	
Characteristics:	Insulation, acid-resistance & corrosion resistant	
Base Materials:	99% Virgin PTFE (Teflon ®) & 1% Pigment.	
Thickness:	0.004" (0.10mm)	
Density:	1.00 – 1.60g/cm ³ (Full Density)	
Longitudinal Tensile:	1,500 – 3,000 PSI	LISTED ALL TAPE
Pressure Rating:	10,000 PSI	
Elongation:	200% & over	YELLOW GAS TAPE
Temperature Range:	-230° C - + 260° C	
Warning Statement:	Do Not Incinerate	
Precautionary Measures:	Best stored at 30° C or below.	
Emergency & First Aid Procedures:	If swallowed, please seek medical attention.	
Hazardous Ingredients:	To the best of our knowledge, this product does not contain any hazardous ingredients.	
Fire Protection:	Melting Point: 330° C Unusual Fire & Explosion Hazards: None known	
Reactivity Data:	Shelf Life: Indefinite Stability: Very Stable Incompatibility: Inert material Hazardous Polymerisation: Does not occur	
Effects of overexposure:	Inhalation, Eyes & Skin: No known effects Chronic: No known chronic effects	
Existing Health effected by Exposure:	No known effects on other illnesses.	
Physical Data:	Specific Gravity: 2.14 – .20g/cm ³	