

REPIPE

Pipe, Connections & Valves

"Connecting Australia"

CLASS 300 BSP GALV HIGH
PRESSURE FITTINGS

ISO 9001 CERTIFIED COMPANY

CLASS 300 BSP GALVANISED HIGH PRESSURE FITTINGS

FEATURES

- Material: Malleable Iron to ASTM A197
- Finish: Hot Dipped Galvanised to AS/NZS 4792
- Threads: ANSI/ ASME B1.201. BSP
- Dimensions: ANSI B16.3 Malleable Iron Thread Fittings
ANSI B16.4 Ferrous Pipe Plugs, Bushing Etc.
ANSI B16.39 Malleable Iron Thread Pipe Unions
- UL Listed

TECHNICAL DATA

- Code: Various (Please see table below)
- Size Range: DN6 – DN 80
- Max Working Pressure: Up to DN25 – 2000psi (UL LISTED)
Up to DN50 – 1500psi (UL LISTED)
Up to DN80 – 1000psi (UL LISTED)
- Temperature Rating: -29°C to 65.5°C
- Tensile Strength: 28.0kgs/ mm2. Min. Or 40,000psu (275 Mpa)
- Elongation: 5% min
- Hardness: 140 Brinnell Max.

RANGE OF PRODUCTS

			
Socket FSG-S2TB-(size DN)	Reducing Socket FSG-S2TB-(size DN)-(size DN)	Union FSG-U2TB-(size DN)	
			
90° Elbow – F&F FSG-E2TB-(size DN)	Tee FSG-T2TB-(size DN)	Reducing Tee FSG-T2TB-(size DN)-(size DN)	Cap FSG-C2TB-(size DN)

SYDNEY- NEWCASTLE – PERTH – 1300 362 954 – sales@repipe.com.au

Distributors of Quality Products Australia Wide