

# REPIPE

Pipe, Connections & Valves

*Connecting Australia*

RETARD CHAMBER

ISO 9001 CERTIFIED COMPANY

## RETARD CHAMBER

### FEATURES

- The Retard Chamber serves primarily as a hydraulic time delay to prevent most false alarms associated with fluctuating water supply pressures.
- Body of the Retarding Chamber has considerable ductility to reduce damage in filed handling.
- All Interior Operating Parts Are Machined From Highly Corrosive-Resistant Alloys, Each Having High Strength and Good Wear Resistance.
- UL Listed
- LPCB Approved



### TECHNICAL DATA

- Code: FFS-RC
- Size Range: ½" NPT Inlet
- Capacity: 3.785 Litres
- Body: High Tensile Cast Iron
- Water Working Pressure Rating: 175 psi
- Factory Tested Hydrostatically: 350 psi

### MATERIALS

DESCRIPTION	MATERIALS	P/N
Outlet Bushing	Cast Iron	323354
Machined Body	Cast Iron	323352
Hex Head Machine Screw	Brass	323357
Cup	Brass	323356
Strainer Screen	Brass	323355
Drain Bushing	Brass	323353

SYDNEY- NEWCASTLE – PERTH – 1300 362 954 – sales@repipe.com.au

*Distributors of Quality Products Australia Wide*

The data provided here is for information purposes only. Repipe reserves the right to change or modify this data without prior notice.

Y:\CATALOGUE & DATA SHEETS - MASTER\Datasheet Masters\FIRE\Retard Chamber.docx