

# REPIPE

Pipe, Connections & Valves

*Connecting Australia*

HIGH PRESSURE PUMP  
CONNECTORS

ISO 9001 CERTIFIED COMPANY

## HIGH PRESSURE PUMP CONNECTORS

### FEATURES

- Made From High Pressure Piping Components Machined To Allow For Expansion, Contraction & Allow for Misalignment
- Compact Design
- Eliminates Vibrations
- Allows For Misalignment 2 to 5 Degrees
- Any Combination of Flange or Thread
- Piping Pressure Rating Maintained
- Preferred Method For Fire Pump Connections




### TECHNICAL DATA

- Code: SSFC-(size)
- Size Range: DN50 – DN300


### DIMENSIONS

CODE	Size DN	A mm	B mm	C mm
SSFC-50	50	120	140	120
SSFC-65	65	120	140	127
SSFC-80	80	120	140	133
SSFC-100	100	120	140	140
SSFC-150	150	130	145	140 *
SSFC-200	200	152	235	
SSFC-250	250	250	280	
SSFC-300	300	250	280	




B

MINIMUM RECOMMENDED  
STYLE - TWO FLEX  
COUPLINGS SUPPLIED  
NOMINATE FLANGE TYPE



A

ANY FLANGE  
COMBINATION –  
MINIMUM FLEX – ONE  
COUPLING SUPPLIED



C

MINIMUM FLEX THREADED X  
FLANGE  
BSP – DN50-150  
NPT – DN50-150  
1 FLEX COUPLING SUPPLIED

SYDNEY- NEWCASTLE – PERTH – 1300 362 954 – sales@repipe.com.au

*Distributors of Quality Products Australia Wide*